15

CLAIMS

What is claimed is:

- 5 1. A method for modeling a behavior of an electrical circuit, comprising: forming a trained neural network which models the behavior of the electrical circuit.
 - 2. A method as in claim 1, comprising:
 statistically covering an entire space for the behavior of the electrical circuit.
 - 3. A method as in claim 2, wherein fully enumerating coverage of the entire space would require more than a predetermined computation time.
 - 4. A method as in claim 3, wherein the predetermined computation time is one week.
- 5. A method as in claim 1, wherein the behavior of the electrical circuit20 comprises power consumption of the electrical circuit.
 - 6. A method as in claim 5, wherein the power consumption of the electrical circuit comprises leakage power of the electrical circuit and switching energy of the electrical circuit.

25

- 7. A method as in claim 1, comprising: using the trained neural network to form a profile of current versus time for the electrical circuit.
- 8. A method as in claim 1, further comprising:
 using the trained neural network to provide input data to a second neural network to form a second trained neural network, wherein the second trained neural network models the behavior of a second circuit, and wherein the second circuit comprises the electrical circuit and other circuitry.
 - 9. A method as in claim 1, wherein the step of forming the trained neural network comprises:

using a non-neural network model of the electrical circuit to generate input data for neural network training.

- 10. A method as in claim 9, wherein the step of forming the trained neural network further comprises:
- using the input data to train a neural network to produce the trained neural network.
 - 11. A method as in claim 9, further comprising: using the input data to train a second neural network.

25

10

15

12. A method for fully modeling a behavior of at least a portion of an electrical circuit, comprising:

selectively modeling the behavior of a portion of the electrical circuit in order to generate a first plurality of cluster values for the behavior of the portion of the electrical circuit;

training a first neural network to form a first trained neural network; generating a first plurality of cluster probabilities using the first trained neural network; and

using the first plurality of cluster probabilities and the first plurality of cluster values, fully modeling the behavior of the portion of the electrical circuit.

13. A method as in claim 12, wherein the behavior comprises power consumption.

14. A method as in claim 13, wherein the power consumption comprises leakage power and switching energy.

15. A method as in claim 12, further comprising:

using the trained neural network to form a profile of current versus time for the portion of the electrical circuit.

10

15

20

16.	A method as in claim 12, further comprising:
	selectively modeling the behavior of the portion of the electrical circuit to
	produce input data for a higher level of modeling;
	using the input data to generate a second plurality of cluster values for the
	behavior of the electrical circuit;
	training a second neural network to form a second trained neural network
	generating a second plurality of cluster probabilities using the second
	neural network; and
	using the second plurality of cluster probabilities and the second plurality
	of cluster values, fully modeling the behavior of the electrical circuit
17.	A method as in claim 12, further comprising:
	performing feature extraction on inputs to the first neural network and on
	inputs to the first trained neural network.
18.	A method for modeling power consumption behavior of an electrical
circ	uit, comprising:
	and another a minurality of almost a marrian values for the algorithms of aircraft

generating a plurality of cluster power values for the electrical circuit; training a neural network to form a trained neural network;

generating a plurality of cluster probabilities using the trained neural network; and

using the plurality of cluster probabilities and the plurality of cluster values, modeling the behavior of the electrical circuit.

- 19. A method as in claim 18, wherein the power consumption behavior of the electrical circuit comprises a leakage power component and a switching energy component.
- 5 20. A method as in claim 18, comprising:
 using the trained neural network to form a profile of current versus time for
 the electrical circuit.